



Austria, A 7143 Apetlon, Söllnergasse 3
 Telefon 02175-3264 (0043 2175-3264)
 office@conpexim.at www.conpexim.at



Kultivator für Weingärten
 steingesichert



mit Ölversorgung



Stockräumergerät



Typ TENKI	Zinken	Arbeitsbreite min./max.	Eigengewicht
SVRK 5 R	5	0,90 m - 1,30 m	470 kg
SVRK 7 R	7	1,20 m - 1,60 m	540 kg
SVRK 9 R	9	1,60 m - 2,00 m	630 kg
SVRK 11 R	11	2,00 m - 2,40 m	730 kg
SVK 7	7	1,50 m - 1,90 m	560 kg
SVK 9	9	2,00 m - 2,40 m	650 kg
SVK 11	11	2,50 m - 2,90 m	775 kg
Serie:	Arbeitstiefe: 15-20 cm, Zinken gefedert - 50*30 mm, Rahmen 80*80 mm, Rahmenhöhe 650 mm, Zinkenabstand SVK 250 mm, SVRK 200 mm, mechanische Breitenverstellung		
Optionen:	Hydraulische Breitenverstellung Rahmen		
	Stabwalze – hydraulisch oder mechanisch breitenverstellbar		
	Stockräumergerät ESBER links/rechts		
	Flügelschare Ala Silver		
	Steilaushebung hydraulisch		
	Zinkenlift hydraulisch		
	Stockräumer Boisselet, mit Ölpumpe, Öltank und Ölkühler		



Steilaushebung hydraulisch